

265 Universal Vinyl Adhesive

DESCRIPTION

Polymer 265 is a water based acrylic emulsion with excellent plasticiser resistance and nonstaining properties. It is protected against bio-degradation, withstands normal wet cleaning practices and is suitable for use over underfloor heating installations.

FOR BONDING

Plasticised vinyl floor and wall coverings and PVC backed carpets.

Polymer 265 is a hard set adhesive suitable for bonding most commercial and domestic vinyl sheeting products vinyl composite tiles, hot press tiles and plank vinyl flooring. It has high initial grab and is ideal for bonding both supported and unsupported PVC vinyl. It may also be used to install hard to hold carpets and those with PVC backings.

SURFACE PREPARATION

To be in accordance with the current Australian Standard "Floor Coverings - 1884-2012 Resilient Sheet & Tiles - Laying & Maintenance Practices" or Australian Standard 2455.2.2007 "Textile Floor Coverings - Installation Practice".

All surfaces to be bonded shall be absorbent, dry, smooth, sound and clean. Subfloors must also be free of wax, grease, paint, previously used adhesive, polish, PVC based membranes and hydrostatic pressure.

The minimum subfloor temperature before commencing surface preparation and adhesive application is 10°C. PE265 can be applied to concrete substrates with moisture contents up to 85% relative humidity tested with the In-Situ Probe method. PE265 can be applied to concrete substrates with pH readings up to 10.0.

Test all concrete substrate flooring for moisture content, according to the current Australian Standards prior to priming or the installation of any floorcoverings.

Indentations and uneven concrete subfloors should be treated with the **Roberts** range of levelling compound and be in accordance with manufacturer's recommendations.

COVERAGE

Approximately 3-5 square metres per litre depending upon the condition and absorbency of the substrate and the type of applicator used.

TECHNICAL DATA

Appearance: Creamy paste

Solids: 70% (approx)

Base Polymer: Acrylic

Carrier: Water

Flammability: Non flammable

Viscosity 60,000 cps (approx)

Toxicity Non toxic

APPLICATION & SPREAD RATE

For the application of vinyl, vinyl planks and vinyl composite tiles it is recommended adhesive to be spread with a 1.6mm "V1" notched trowel giving a spread rate up to 5 square metres per litre.

Hard to hold carpets installed indoors, 3.2mm "V3" notched trowel giving a spread rate up to 2 square meters per litre.

Spread adhesive with the recommended notched trowel.

The application, use and processing of our products is the responsibility of the user. Any technical or other advice, information or data provided by us, whether verbally, in writing or by way of trials or tests, is given without guarantee or warranty. Refer to Material Safety Data Sheets for information on Storage & Handling, Health and Safety, and Transport.

RLA POLYMERS PTY LTD

ACN 004 739 915


215 Colchester Road, Kilsyth, Victoria 3137 Australia

P.O. Box 147, Kilsyth, Victoria 3137 Australia

Telephone: (03) 9728 1644 • Facs/mile: (03) 9728 6009

E-mail: info@rlapolymers.com.au • Web: www.rlagroup.com.au





Allow adhesive to develop some initial tack – generally 5-10minutes at 20°C before lowering floorcovering into the wet film of adhesive and rolled to ensure transfer has occurred. Tack-up time will depend upon atmospheric conditions and substrate absorbency. Complete installation according to vinyl manufacturer's instructions, ensuring the installation is rolled in both directions with the recommended roller weight, prior to the adhesive setting. Do not allow heavy traffic for 24 hours. All seams for domestic vinyl should be seam sealed with Roberts 5601 Vinyl Seam Sealer.

CLEAN UP

Clean tools immediately after use with warm soapy water. Dried adhesive may be cleaned off using R550 Latex/Acrylic Adhesive Remover applied to a damp cloth then rubbed gently over the dried adhesive or alternatively please use AFTEK Handy Wipes.

SHELF LIFE

12 -14 months in unopened containers stored out of direct sunlight.

STORAGE

Keep in well ventilated areas stored out of direct sunlight.

CONTAINER SIZES

15 litre plastic containers

SAFETY & HANDLING

A Safety Data Sheet is available on request.

FIRST AID

For advice contact a Poison Information Centre (Australia PH: 13 11 26 , New Zealand PH: 0800 764 766) or a doctor at once. A Material Safety Data Sheet is available on request.

The application, use and processing of our products is the responsibility of the user. Any technical or other advice, information or data provided by us, whether verbally, in writing or by way of trials or tests, is given without guarantee or warranty. Refer to Material Safety Data Sheets for information on Storage & Handling, Health and Safety, and Transport.

RLA POLYMERS PTY LTD


ACN 004 739 915

215 Colchester Road, Kilsyth, Victoria 3137 Australia

P.O. Box 147, Kilsyth, Victoria 3137 Australia

Telephone: (03) 9728 1644 • Facs/mile: (03) 9728 6009

E-mail: info@rlapolymers.com.au • Web: www.rlagroup.com.au



Warranty Statement

RLA Polymers guarantees this product against manufacturing defects and guarantees it to be manufactured to our published specification.

We certify that when fully cured this product is suitable for use and will perform as described in our technical data sheet or other published materials.

RLA Polymers will replace product free of charge when purchased from any legally verifiable source, and where product is proven to have been stored, handled and installed according to instructions published on our packaging and within the stated shelf life. The installation of all materials must be carried out in accordance with the relevant Australian Standard and the Floorcovering Manufacturers instructions and the floorcoverings must have been subject to normal traffic conditions.

Warranty doesn't not apply if damage, loss, failure to follow instructions or other circumstances are out of our control.

Sufficient time and access to investigate any complaint must be accorded to RLA Polymers. The consumer is responsible for any expenses incurred in making a claim.

A claim form can be requested by:

Phone: 1800 242 931

Email: info@rlapolymers.com.au

Mail: 215 Colchester Road Kilsyth Victoria 3137 (attn Customer Service)

Australian Consumer Law

Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure. The benefits under our warranty are in addition to other rights and remedies available to the consumer under the law in relation to the goods and services to which the warranty relates.

Disclaimer

All Statements and technical information contained herein are based on tests we believe to be reliable but the accuracy thereof is not guaranteed.

Users assume all risk and liability resulting from the use of the product and must confirm the suitability thereof by their own tests.

Conditions of Sale contain a limited warranty against manufacturing defects

Issued: July 2016

The application, use and processing of our products is the responsibility of the user. Any technical or other advice, information or data provided by us, whether verbally, in writing or by way of trials or tests, is given without guarantee or warranty. Refer to Material Safety Data Sheets for information on Storage & Handling, Health and Safety, and Transport.

RLA POLYMERS PTY LTD

ACN 004 739 915

215 Colchester Road, Kilsyth, Victoria 3137 Australia

P.O. Box 147, Kilsyth, Victoria 3137 Australia

Telephone: (03) 9728 1644 • Facs/mile: (03) 9728 6009

E-mail: info@rlapolymers.com.au • Web: www.rlagroup.com.au

