



PRODUCT
DATA

R59 CARPET ADHESIVE

PRODUCT DESCRIPTION

Roberts 59 Carpet Adhesive is water-based and specifically formulated to provide a tacky film of adhesive that is strong enough to eliminate any movement in the carpet after the installation is completed. It is suitable for both Double Bond and Direct Stick installations. The adhesive offers a quick grab and has sufficient working time for smaller and larger installations.

FOR BONDING

Roberts 59 Carpet Adhesive is designed to be used for bonding both slab dual bond underlay to the subfloor and the carpet to the slab underlay. It is suitable for adhering Hessian back, Tufted back, most backed woven carpets, woven polypropylene and jute sided latex foam laminated slab underlays.

Note: Not recommended to adhere fusion bonded carpets. Do not thin adhesive.

SURFACE PREPARATION

To be in accordance with the Australian Standards 2455.1.2007 "Textile Floor Coverings Installation Practice". All surfaces to be bonded to should be absorbent, dry, smooth, sound and clean. Subfloors should be free from wax, grease, paints, previously used adhesive, hydrostatic pressure, polishes, PVC base membranes, laitance (being the dusty unstable topping of poorly or insufficiently cured concrete) and any other impurities or contaminants that may affect adhesion. The minimum subfloor temperature before commencing installation should be 10°C.

It is recommended that all highly absorbent concrete floors are to be primed with R400 Floor & Wall Primer prior to the application of adhesive.

All concrete substrate floors should be tested for moisture content according to the relevant Australian Standards prior to installation. Indentations and uneven concrete subfloors should be treated with the Roberts range of levelling compound and be in accordance with manufacturer's recommendations.

APPLICATION

Spread adhesive with the recommended notched trowel.

Approximately 2-4 square metres per litre depending upon the size of the notched trowel used and absorbency of the substrate.

The notching recommended is 1.6mm (V1) for underlay to subfloor, 2.4mm (V2) for Hessian backed carpets and 3.2mm (V3) for Action Bac, woven or highly textured backings.

A strong tack develops enabling carpet/underlay to be lowered in almost immediately at temperatures in excess of 15°C. In colder conditions, allow adhesive to remain open until tack and grab develop then lower in the carpet/underlay into the wet film of adhesive. Check to ensure transfer of adhesive to the carpet/underlay has occurred. Roll the finished installation with a 25-35kg roller. Complete the installation according to manufacturer's instructions.

Do not allow heavy traffic for 24 hours.

**adhesives hot melts tapes
levelling powders primers**

The application, use and processing of our products is the responsibility of the user. Any technical or other advice, information or data provided by us, whether verbally, in writing or by way of trials or tests, is given without guarantee or warranty. Refer to Material Safety Data Sheets for information on Storage & Handling, Health and Safety, and Transport.

RLA POLYMERS PTY LTD

ACN 004 709 915

215 Colchester Road, Kilsyth, Victoria 3137 Australia

P.O. Box 147, Kilsyth, Victoria 3137 Australia

Telephone: (03) 9728 1644 • Facs mile: (03) 9728 6009

E-mail: info@rlapolymers.com.au • Web: www.rlagroup.com.au





PRODUCT
DATA

CLEAN UP

Clean tools immediately after use with warm soapy water. Dried adhesive may be cleaned off using Roberts 900 Thinners applied to a damp cloth then rubbed gently over the dried adhesive. For removing old adhesives from the floor prior to the laying new vinyl it is recommended Roberts 550 Latex/Acrylic Adhesive Remover be used.

Roberts 550 is not recommended for removing adhesive from vinyl, carpet or painted surfaces.

STORAGE/ HANDLING

For optimum shelf life store in tightly closed original containers out of direct sunlight. Keep container tightly closed. Store Locked up.

CONTAINER SIZE

15 litre plastic pails

SHELF LIFE

12-14 months in unopened containers stored out of direct sunlight.

SAFETY & HANDLING

A Safety Data Sheet is available upon request.

Disposal

Please dispose of empty containers and residue in accordance with your local waste management regulations.

First Aid

In use, please ensure that Occupational Health and Safety requirements are observed.

Eyes: Irrigate with water for 10 minutes and see a doctor.

Skin: Wash off with warm water and soap.

If swallowed, give plenty of water. Do not induce vomiting. Seek medical attention.

adhesives hot melts tapes
levelling powders primers

The application, use and processing of our products is the responsibility of the user. Any technical or other advice, information or data provided by us, whether verbally, in writing or by way of trials or tests, is given without guarantee or warranty. Refer to Material Safety Data Sheets for information on Storage & Handling, Health and Safety, and Transport.

RLA POLYMERS PTY LTD

ACN 004 709 915

215 Colchester Road, Kilsyth, Victoria 3137 Australia

P.O. Box 147, Kilsyth, Victoria 3137 Australia

Telephone: (03) 9728 1644 • Facs/mile: (03) 9728 6009

E-mail: info@rlapolymers.com.au • Web: www.rlagroup.com.au





Warranty Statement

RLA Polymers guarantees this product against manufacturing defects and guarantees it to be manufactured to our published specification.

We certify that when fully cured this product is suitable for use and will perform as described in our technical data sheet or other published materials.

RLA Polymers will replace product free of charge when purchased from any legally verifiable source, and where product is proven to have been stored, handled and installed according to instructions published on our packaging and within the stated shelf life. The Installation of all materials must be carried out in accordance with the relevant Australian Standard and the Floorcovering Manufacturers instructions and the floorcoverings must have been subject to normal traffic conditions.

Warranty doesn't not apply if damage, loss, failure to follow instructions or other circumstances are out of our control.

Sufficient time and access to investigate any complaint must be accorded to RLA Polymers.

The consumer is responsible for any expenses incurred in making a claim.

A claim form can be requested by:

Phone: 1800 242 931

Email: info@rlapolymers.com.au

Mail: 215 Colchester Road Kilsyth Victoria 3137 (attn Customer Services)

Australian Consumer Law

Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage.

You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.

The benefits under our warranty are in addition to other rights and remedies available to the consumer under the law in relation to the goods and services to which the warranty relates.

Disclaimer

All Statements and technical information contained herein are based on tests we believe to be reliable but the accuracy thereof is not guaranteed.

Users assume all risk and liability resulting from the use of the product and must confirm the suitability thereof by their own tests.

Conditions of Sale contain a limited warranty against manufacturing defects.

Issued: July 2016

The application, use and processing of our products is the responsibility of the user. Any technical or other advice, information or data provided by us, whether verbally, in writing or by way of trials or tests, is given without guarantee or warranty. Refer to Material Safety Data Sheets for information on Storage & Handling, Health and Safety, and Transport.

RLA POLYMERS PTY LTD

ACN 004 709 915

215 Colchester Road, Kilsyth, Victoria 3137 Australia

P.O. Box 147, Kilsyth, Victoria 3137 Australia

Telephone: (03) 9728 1644 • Facs mile: (03) 9728 6009

E-mail: info@rlapolymers.com.au • Web: www.rlagroup.com.au



adhesives hot melts tapes
levelling powders primers

