



R679 CARPET LATEX

Description:

Roberts 679 Carpet Latex is a compounded latex product used for the sealing of raw edges, strengthening worn backing, replacing damaged nap and adhering pad underlays to Subfloors.

Application:

Back Seaming

Lay carpet face down with seam edges butted tightly. Use stay tacks to hold the carpet in place. Apply a liberal amount of latex to the areas to be seamed and spread evenly. Lay a strip of plain woven carpet seaming tape into the latex and recoat with a second application of latex. The latex should thoroughly wet the tape fibres and the carpet backing to ensure a good bond. Allow the carpet to dry in position for 4-5 hours then remove stay tacks and install.

Face Seaming

Lay carpet face up with seam edges butted tightly. Use stay tacks to hold the carpet in place. Insert paper-backed carpet seaming tape under the carpet and centre it under the seam area. Apply a liberal coat of latex to the tape and spread evenly. Apply a uniform coat of latex to the carpet backing area that will be seamed. The latex should thoroughly wet the tape fibres and the carpet backing to ensure a good bond. Allow the carpet to dry in position for 4-5 hours then remove stay tacks and install.

Sealing Selvedge

Prior to Heat Bond seaming, most tufted and woven carpets are prone to lose tufts or unravel after the selvedge is trimmed. It is recommended Carpet Latex be applied to the edge of the seam prior to Head Bond Seaming. Work latex into the edge and allow to dry before seaming.

Domestic underlays

Apply a liberal amount latex to a dry, clean, sound and smooth substrate. Place underlay into the wet latex install underlay in accordance to manufactures recommendations.

Clean Up

Clean tools immediately after use with warm soapy water. Dried adhesive may be cleaned off using Roberts 550 Latex/Acrylic Remover applied with a damp cloth then rubbed gently over the dried adhesive.

Shelf Life

6 months in sealed container out of direct sunlight

Solids

60% approx.

Packaging

15 & 5 & 1 litre

Tack-Up: Typically 2-4 hours (depending on temperature of slab and ventilation)

Safety & Handling

A Safety Data Sheet available upon request.

The application, use and processing of our products is the responsibility of the user. Any technical or other advice, information or data provided by us, whether verbally, in writing or by way of trials or tests, is given without guarantee or warranty. Refer to Material Safety Data Sheets for information on Storage & Handling, Health and Safety, and Transport.

RLA POLYMERS PTY LTD

ACN 004 709 915

215 Colchester Road, Kilsyth, Victoria 3137 Australia

P.O. Box 147, Kilsyth, Victoria 3137 Australia

Telephone: (03) 9728 1644 • Facs/mile: (03) 9728 6009

E-mail: info@rlapolymers.com.au • Web: www.rlagroup.com.au



adhesives hot melts tapes
levelling powders primers





Warranty Statement

RLA Polymers guarantees this product against manufacturing defects and guarantees it to be manufactured to our published specification.

We certify that when fully cured this product is suitable for use and will perform as described in our technical data sheet or other published materials.

RLA Polymers will replace product free of charge when purchased from any legally verifiable source, and where product is proven to have been stored, handled and installed according to instructions published on our packaging and within the stated shelf life. The Installation of all materials must be carried out in accordance with the relevant Australian Standard and the Floorcovering Manufacturers instructions and the floorcoverings must have been subject to normal traffic conditions.

Warranty doesn't not apply if damage, loss, failure to follow instructions or other circumstances are out of our control.

Sufficient time and access to investigate any complaint must be accorded to RLA Polymers.

The consumer is responsible for any expenses incurred in making a claim.

A claim form can be requested by:

Phone: 1800 242 931

Email: info@rlapolymers.com.au

Mail: 215 Colchester Road Kilsyth Victoria 3137 (attn Customer Services)

Australian Consumer Law

Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage.

You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.

The benefits under our warranty are in addition to other rights and remedies available to the consumer under the law in relation to the goods and services to which the warranty relates.

Disclaimer

All Statements and technical information contained herein are based on tests we believe to be reliable but the accuracy thereof is not guaranteed.

Users assume all risk and liability resulting from the use of the product and must confirm the suitability thereof by their own tests.

Conditions of Sale contain a limited warranty against manufacturing defects.

Issued: July 2016

The application, use and processing of our products is the responsibility of the user. Any technical or other advice, information or data provided by us, whether verbally, in writing or by way of trials or tests, is given without guarantee or warranty. Refer to Material Safety Data Sheets for information on Storage & Handling, Health and Safety, and Transport.

RLA POLYMERS PTY LTD

ACN 004 709 915

215 Colchester Road, Kilsyth, Victoria 3137 Australia

P.O. Box 147, Kilsyth, Victoria 3137 Australia

Telephone: (03) 9728 1644 • Facs/mile: (03) 9728 6009

E-mail: info@rlapolymers.com.au • Web: www.rlagroup.com.au



adhesives hot melts tapes
levelling powders primers

